



204-453-000-011

IQS453 Signal Conditioner, 5 m TQ4X3 System

Product scope

- Matches the TQ4X3 probe for a 12 mm nominal measuring range.
- Provides 1.33 mV/ μ m sensitivity through a standard three-wire voltage output.
- Uses the 5 m matched cable ordering option shown for this conditioner.

Manufacturer source

Vibro-Meter IQS 451, 452 and 453 proximity signal conditioner data sheet, document 265-254.

This web-optimized copy contains only verified information relevant to the stated ordering code.

Request a fast quote	Product reference	
Email: info@apterpower.com Phone: +86 18106909650 apter.com/inquiry.php	204-453-000-011	

The enclosed manufacturer pages are reproduced without alteration to technical content. External interactive links and unrelated pages are excluded from this web-optimized copy.

204-453-000-011 verified configuration

IQS453 Signal Conditioner, 5 m TQ4X3 System

Exact product identity

Vibro-Meter 204-453-000-011 is the standard IQS453 three-wire voltage conditioner for a TQ4X3 long-range probe with a 5 m matched cable.

Product classification

Manufacturer: Vibro-Meter

Product family: IQS 451 / 452 / 453 Proximity Signal Conditioners

Product type: Proximity Signal Conditioner

Installation attention

204-453-000-011: Do not substitute the shorter-range IQS451 or IQS452 calibration; the TQ4X3 probe and 1.33 mV/ μ m sensitivity define this chain.

204-453-000-011 technical specifications

Verified product data · section 1 of 3

Parameter	Verified value
Ordering number	204-453-000-011
Conditioner model	IQS453
Matching probe family	TQ4X3
Nominal measuring range	12 mm
Output mode	3-wire voltage output
Sensitivity	1.33 mV/μm
Matched probe cable length	5 m
Version	Standard
Signal conditioner family	IQS 451 / 452 / 453
Measurement principle	Eddy current proximity
Signal method	HF modulator/demodulator
Matching probes	Vibro-Meter TQ 400 series

204-453-000-011 technical specifications

Verified product data · section 2 of 3

Parameter	Verified value
Frequency response	DC to 20 kHz (-3 dB)
Interchangeability	≤5%
Voltage output impedance	500 Ω
Voltage-output short-circuit current	45 mA
Current output at minimum gap	15 mA
Current output at maximum gap	20 mA
Current-output dynamic range	5 mA
Supply voltage	-20 to -32 V
Supply current	13 ±1 mA; 25 mA maximum
Operating temperature	-30 to +70°C
Storage temperature	-40 to +80°C
Humidity	95% maximum, non-condensing

204-453-000-011 technical specifications

Verified product data · section 3 of 3

Parameter	Verified value
Vibration resistance	2 g peak, 10 to 500 Hz
Protection class	IP40
Housing	Anodized injection-moulded aluminium
Standard weight	Approximately 140 g

204-453-000-011 application and integration guide

IQS 451 / 452 / 453 Proximity Signal Conditioners

Applications

- Measures relative shaft vibration and static gap without contacting the rotating surface.
- Conditions proximity signals for turbine, compressor, pump and generator monitoring systems.
- Feeds rack processor modules with a temperature-compensated output scaled to probe movement.

Model-specific integration points

Proximity Measurement

- The matched TQ4X3 chain measures up to 12 mm of probe-to-target gap movement.
- DC response supports static gap observation as well as dynamic shaft displacement.
- Interchangeability is specified within five percent when the documented chain is preserved.

Dynamic Response

- The conditioner response extends from DC to 20 kHz at the -3 dB point.
- A 1.33 mV/μm voltage scale converts target movement into the three-wire output.
- The eddy-current principle measures movement without physical contact with the target.

Environmental Ratings

- Normal operation is specified from -30 to +70°C.
- The potted aluminium housing is rated IP40 and resists dust and moisture ingress inside a suitable enclosure.
- Operation and storage allow up to 95% relative humidity without condensation.

204-453-000-011 manufacturer source record

Vibro-Meter IQS 451, 452 and 453 proximity signal conditioner data sheet, document 265-254.

Source used for verification

Vibro-Meter IQS 451, 452 and 453 proximity signal conditioner data sheet, document 265-254.

Manufacturer document location

<https://catalogue.meggittsensing.com/>

Editorial scope

Technical values are preserved from the cited manufacturer material and limited to the product or documented family configuration.

No third-party sales claims, unrelated product pages, external hyperlinks or non-Apter contact details are included.



GLOBAL INDUSTRIAL AUTOMATION SOURCING

Ready to source this part?

Ask for availability, pricing and delivery options.

Request a fast quote

Include the product title and any required part number or quantity.

EMAIL

info@apterpower.com

PHONE

+86 18106909650

REQUEST A QUOTE

PRODUCT: 204-453-000-011



SCAN TO CHAT ON WHATSAPP

Manufacturer pages are reproduced without alteration to technical content.

Apter Power is not an authorized distributor, reseller or representative of the products featured.