

VERIFIED PRODUCT REFERENCE

Siemens 6ES5420-4UA13 Digital Input Module

Siemens 6ES5420-4UA13 is a SIMATIC S5 420 digital input module with 32 inputs and 24 V DC field service. It is documented for legacy S5-135U/155U installations.

Manufacturer Siemens	Product family SIMATIC S5-135U/155U Digital I/O	Exact model 6ES5420-4UA13
-------------------------	--	------------------------------

Officially documented specifications

Module designation	420
I/O function	digital input
Channel capacity	32 inputs
Field electrical class	24 V DC
Isolation	Non-isolated
System bus current	5 V, 80 mA typical
Power dissipation	7.0 W
Dimensions (W x H x D)	20 x 255 x 195 mm
Weight	Approx. 0.4 kg
Permissible unshielded line	As documented in the Siemens system manual
Enable circuit	Front enable input/jumper arrangement
Host systems	SIMATIC S5-135U / S5-155U
Rated input current	8.5 mA
Typical input delay	3 ms
Input resistance	2.8 kohm typical

INSTALLATION AND PROCUREMENT REFERENCE

6ES5420-4UA13 application guidance

6ES5420-4UA13 is the Siemens SIMATIC S5 420 digital input module documented with 32 inputs. The field-side electrical class is 24 V DC, and the official manual identifies non-isolated isolation behavior.

The board transfers discrete states between the S5 process image and connected machinery wiring. Its channel grouping, enable circuit and diagnostic indications are integral to the installed cabinet design.

Retrofit work must preserve front-connector numbering, commons, supply polarity, enable jumper, addressing and external suppression. Similar 6ES5 modules can differ in voltage, width, current or protection and require a line-by-line comparison.

High-risk technical note

6ES5420-4UA13 requires the documented 24 V DC field arrangement; verify the enable circuit, commons and connector numbering before moving any conductor.

Manufacturer source record

- Siemens SIMATIC S5 System Manual, module sheet for 6ES5420-4UA13
- User-supplied Siemens official extract verified against the model text



Request a quotation for 6ES5420-4UA13

Email: info@apterpower.com

Phone: +86 18106909650

Include the complete nameplate, quantity, destination, and required delivery date.

Prepared from the manufacturer references listed above. Verify the latest revision and the complete installed configuration before replacement or commissioning.