SIEMENS

Data sheet 6GK1503-2CA00

Product type designation

PROFIBUS OLM P11

PROFIBUS OLM/P11 V4.0 Optical Link module with 1 RS485 and 1 plastic FOC interface (2 BFOC sockets), with signaling contact and test port



Transmission rate	
Transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
Transfer rate / with PROFIBUS PA	45.45 kbit/s
Interfaces	
Number of electrical/optical connections / for network components or terminal equipment / maximum	2
Number of electrical connections	
• for network components or terminal equipment	1
• for measuring device	1
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
Type of electrical connection	
• for network components or terminal equipment	9-pin Sub-D socket
• for measuring device	2-pole terminal block
• for power supply	-
• for power supply and signaling contact	5-pole terminal block
Number of optical interfaces / for fiber optic cable	1

Subject to change without notice
© Copyright Siemens

Design of the optical interface / for fiber optic cable	BFOC port

Optical data	
Damping ratio / of the FOC transmission link	
• for POF FOC with 980/1000 µm / at 230 dB/km	13 dB
propagation delay [bit]	6.5 bit
Connectable optical power relative to 1 mW	
• of the FOC transmission link / for PCF FOC with 200/230 µm / at 10 dB/km	-17 dB
• of the FOC transmission link / for POF FOC with 980/1000 µm / at 230 dB/km	-5 dB
Optical sensitivity relating to 1 mW	
• of the FOC transmission link / for PCF FOC with 200/230 µm / at 10 dB/km	-25 dB
• of the FOC transmission link / for POF FOC with 980/1000 µm / at 230 dB/km	-25 dB
Wavelength	
• of the FOC transmission link / for PCF FOC with 200/230 µm / at 10 dB/km	660 nm
• of the FOC transmission link / for POF FOC with 980/1000 µm / at 230 dB/km	660 nm
Wire length	
• for PCF FOC with 200/230 µm / at 10 dB/km / maximum	400 m
• for POF FOC with 980/1000 µm / at 230 dB/km / maximum	80 m

Signal-Inputs/outputs	
Operating voltage / of the signaling contacts / at DC / Rated value	24 V
Operating current / of the signaling contacts / at DC / maximum	0.1 A

Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage / at DC / Rated value	24 V
Supply voltage / at DC	18.8 ... 28.8 V
Product component / fusing at power supply input	Yes
Consumed current / at DC / at 24 V / maximum	0.2 A

Permitted ambient conditions	
Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %

Subject to change without notice
© Copyright Siemens

Protection class IP	IP40

Design, dimensions and weight	
Design	compact
Width	39.5 mm
Height	112 mm
Depth	74.5 mm
Net weight	340 g
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes

Product functions / Redundancy	
Product function / Ring redundancy	Yes

Standards, specifications, approvals	
Standard	
• for FM	FM3611: Class 1, Division 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4
• for hazardous zone	EN 60079-0: 2006, EN60079-15: 2005, EN60079-28: 2007, II 3 (2) G Ex nA [opis] IIC T4 KEMA 09 ATEX 0173X
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 Nr. 60950-1
• for hazardous zone / from CSA and UL	UL 1604 and UL 2279-15 (Hazardous Location), CSA C22.2 No. 213-M1987, Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
Certificate of suitability	EN 61000-6-2, EN 61000-6-4
• CE marking	Yes
• C-Tick	Yes
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	Yes
• Germanische Lloyd (GL)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes

Further Information / Internet Links	
Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter

Subject to change without notice
© Copyright Siemens

• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	07/10/2019

Subject to change without notice
© Copyright Siemens