

330903-00-07-10-01-CN

3300 XL NSv Proximity Probe

Product identification

Bently Nevada 330903-00-07-10-01-CN is a 3300 XL NSv proximity probe with M8 x 1 threads, without armor, 0 mm unthreaded length, 70 mm case length and a 1.0 m (39 in) lead.

Parameter	Verified value
Manufacturer	Bently Nevada
Model	330903-00-07-10-01-CN
Product Family	3300 XL NSv Proximity Transducer System
Product Type	Proximity Probe

Technical specifications

Parameter	Verified value
Thread	M8 x 1
Armor	Without armor
Unthreaded length	0 mm
Overall case length	70 mm
Total probe length	1.0 m (39 in)
Connector and cable	01 = ClickLoc with connector protector, standard cable
Agency approval	CN = retained; not defined in Datasheet 147385 Rev. R
System linear range	1.5 mm (60 mils)
Nominal scale factor	7.87 V/mm (200 mV/mil)
Reference target	AISI 4140 steel, 31 mm minimum diameter
System power	-17.5 to -26 VDC without barriers; 12 mA maximum
Output resistance	50 ohms
Extension-cable capacitance	69.9 pF/m typical
Maximum field-wire length	305 m (1000 ft)
Probe-to-cable pull strength	220 N (50 lb)
Connector family	Gold-plated brass ClickLoc
Relative humidity	100% condensing, non-submersible with protected connectors
Proximitor operating temperature	-52 to +100 C
Recommended field wiring	Three-conductor shielded triad

Product overview

330903-00-07-10-01-CN is a M8 x 1 without armor probe in the Bently Nevada 3300 XL NSv proximity transducer family. The 0 mm unthreaded section and 70 mm overall case define its fit and sensing reach.

The probe carries a 1.0 m (39 in) lead with 01 = clickloc with connector protector, standard cable. Its narrow-side-view eddy-current geometry is intended for small targets and close-clearance measurements where a standard 5 mm or 8 mm system may not fit.

When paired with the correct NSv extension cable and Proximitor Sensor, the configuration supports vibration, position and timing measurements on rotating machinery. The full ordering code must be retained because thread, armor, length, cable and approval fields are not interchangeable.

Applications

- Measures radial shaft vibration in compact compressor or rotating-machine installations.
- Tracks axial shaft position where restricted target size favors the narrow-side-view NSv system.
- Provides Keyphasor, tachometer or zero-speed input from an appropriate rotating target.

Connection Details

- The selected cable termination is 01 = clickloc with connector protector, standard cable.
- Connector protector status for this code is included by the connector option.
- Mate only clean, dry ClickLoc surfaces and verify full locking engagement.

Operating Environment

- The NSv Proximitor operates from -52 to +100 C under the published conditions.
- Protected connectors support condensing humidity but the assembly is not submersible.
- Chemical-resistant probe construction supports many process-compressor installations.

Replacement Checks

- Match the complete five-field ordering code rather than the base probe number alone.
- Confirm thread, case reach, armor, cable length and connector option against the removed item.
- Treat the final approval field only according to the supplied label and current approval guide.

High-risk technical note

330903-00-07-10-01-CN must be matched by full thread, case, cable and connector identity; do not infer agency approval from an undocumented CN suffix.

Request a quotation
info@apterpower.com
+86 18106909650

Exact model
330903-00-07-10-01-CN
3300 XL NSv Proximity Transducer System



Manufacturer source

<https://dam.bakerhughes.com/m/7a79b853504f738/original/3300-XL-NSv-Proximity-Transducer-System-Datasheet-147385-pdf.pdf>
Source technical meaning is unchanged. This web edition is organized for exact-model identification and quotation support.