External Connectors	
Primary Power	DC Input, 3-wire

LocalBus Isolator

The DeltaV LocalBus Isolator protects the I.S. I/O from fault voltages from AC main power supplies. The LocalBus Isolator also links intrinsically safe I/O with non-intrinsically-safe I/O. The following table gives the specifications for the DeltaV LocalBus Isolator.

LocalBus Isolator Specifications		
Dimensions	**Centimeters**	**Inches**
Height	11.0	4.3
Width	4.2	1.7
Depth	16.0	6.2
Weight	250 grams	8.7 oz

Carriers

All DeltaV I.S. I/O cards are contained in modular 8-wide carriers. Connect the carriers in the most efficient configuration for your plant. The carriers have multi-pin connectors to ensure that I.S. I/O is never connected to non-I.S. I/O.

Power supplies for I.S. I/O modules using field wiring have their own modular carriers. These carriers connect between the I/O carriers.

Use a LocalBus isolator to connect I.S. I/O with non-I.S. field wiring. The LocalBus isolator resides on its own carrier.

Carrier Specifications

Common Environmental Specifications for all Carriers	
Category	**Specifications**
Relative Humidity	5 to 95%, Non-condensing
Airborne Contaminants	ISA-S71.04-1985 Airborne Contaminants Class G3
Protection Rating	IP 20
Shock	10 g ½-sine Wave for 11 ms

info@apterpower.com +86 18106909650 SOURCE PAGE 7 / 9 WHATSAPP QUOTE >

M-series Intrinsically Safe I/O

July 2023

Vibration	1 mm peak-to-peak from 5 to 16 Hz; 0.5 g from 16 to 150 Hz
Hazardous Area/Location*	Zone 2 IIC T4 hazardous areas Class I, Div 2, Groups A, B, C, D T4 hazardous locations.

*Refer to Zone 0 installation instructions (12P1990) for information on installing in hazardous areas.

8-Wide I.S. I/O Carrier Specifications		
Capacity	Eight I/O Cards and Eight Terminal Blocks	
Dimensions	**Centimeters**	**Inches**
Height	16.5	6.5
Width	33.6	13.2
Depth	3.1	1.2

I.S. I/O Power Supply Carrier Specifications		
Capacity	One I.S. Power Supply	
Dimensions	**Centimeters**	**Inches**
Height	16.5	6.5
Width	8.4	3.3
Depth	3.1	1.2

LocalBus Isolator Carrier Specifications		
Capacity	One LocalBus Isolator	
Dimensions	**Centimeters**	**Inches**
Height	16.5	6.5
Width	8.4	3.3
Depth	3.1	1.2

I.S. 1-wide Carrier Extender (Left and Right) Specifications		
Capacity	Single Cable	
Dimensions	**Centimeters**	**Inches**
Height	16.5	6.5
Width	4.2	1.7
Depth	3.1	1.2

info@apterpower.com
+86 18106909650
SOURCE PAGE 8 / 9
WHATSAPP QUOTE >

System Compatibility

M-series I/O cards are not compatible with S-series Controllers and Carriers.

Ordering Information

Description	Model Number
8-channel AI, 4-20 mA with HART with I/O Term Block with Loop Disconnect Term Block	 VE4012S2B1 VE4012S2B2
8-channel AO, 4-20 mA with HART with I/O Term Block with Loop Disconnect Term Block	 VE4013S2B1 VE4013S2B2
16-channel DI, Switch/Proximity Detector	VE4010B1
4-channel, DO, Solenoid Driver, IIC Gas Groups with I/O Term Block with Loop Disconnect Term Block	 VE4011B1 VE4011B2
8-wide Carrier without Carrier Extension Cable with Carrier Extension Cable	VE4060C0 VE4060C1
24 VDC Input I/O Module Supply and Carrier	VE5010
LocalBus Isolator and Carrier	VE4070

©2023, Emerson. All rights reserved.

The Emerson logo is a trademark and service mark of Emerson Electric Co. The DeltaV logo is a mark of one of the Emerson family of companies. All other marks are the property of their respective owners.

The contents of this publication are presented for informational purposes only, and while diligent efforts were made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice.

Contact Us
www.emerson.com/contactus

DELTAV™

EMERSON™

GLOBAL INDUSTRIAL AUTOMATION SOURCING

Ready to source this part?

Ask for availability, pricing and delivery options.

Request a fast quote

Include the product title and any required part number or quantity.

EMAIL

info@apterpower.com

PHONE

+86 18106909650

CHAT ON WHATSAPP >

SCAN TO CHAT ON WHATSAPP

PRODUCT: VE4060C0 / DeltaV M-series 8-Wide Intrinsically Safe I/O Carrier without Extension Cable

The enclosed manufacturer pages are reproduced without alteration to technical content.

Apter Power is not an authorized distributor, reseller or representative of the products featured.

Product names, trademarks, brands and logos remain the property of their respective owners.