

TERMINATION ASSEMBLIES AND CABLES

General Description

Field I/O signals connect to the FBM subsystem via DIN rail mounted termination assemblies (TAs). Multiple types of TAs are available with FBMs to provide I/O signal connections, signal conditioning, optical isolation from signal surges, external power connections, and/or fusing for protection of the FBM and/or field device as required by the particular FBM. Since these features are built into the termination assemblies (where required), in most applications there is no need for additional termination equipment for field circuit functions such as circuit protection or signal conditioning (including fusing and power distribution).

The termination assembly can be used with a single FBM207 or with a redundant pair (two FBM207s).

The DIN rail mounted termination assemblies connect to the FBM subsystem baseplate by means of removable termination cables. When used with a redundant module pair, the termination assembly is connected to the baseplate using a redundant adapter (RH926ZY (supersedes P0926ZY)). The DIN rail mounted TAs connect to the redundant adapter by means of a removable termination cable.

The cables for both single and redundant configurations are available in a variety of lengths, up to 30 meters (98 feet), allowing the termination assemblies to be mounted in either the enclosure or in an adjacent enclosure. Refer to Table 2 on page 12 for termination cable part numbers and specifications.

Discrete Inputs

Termination assemblies with discrete inputs support sixteen 2-wire discrete input signals at passive low voltage levels of less than 60 V DC and active high voltage levels of 125 V DC, 120 V AC, or 240 V AC. Active termination assemblies support input signal conditioning for FBMs. To condition signals, these termination assemblies may provide optical isolation, current limiting, noise reduction, voltage attenuation, or optional terminal blocks to connect externally supplied excitation voltage.

Low Voltage Discrete Inputs

The low voltage inputs (less than 60 V DC) use passive termination assemblies. Inputs for FBM207 are voltage monitor types. Voltage monitor inputs require an external field voltage source. Contact sense inputs use the FBM auxiliary +24 V DC or +48 V DC, supplied to all input channels on the assembly, to wet field contacts.

A load may not be required for proper operation of the input channels. A diode may be required for a DC inductive load only.

High Voltage Discrete Inputs

The high voltage input circuits support 125 V DC, 120 V AC, or 240 V ac. Inputs can be either voltage monitor or switched types. Voltage monitor inputs require a field voltage source. Switch inputs use customer supplied excitation voltage applied to dedicated terminals on the termination assembly and distributed on the termination assembly to each of the input channels.

To condition signals, voltage attenuation circuits are located on daughter boards mounted under the component covers of the termination assemblies.

Table 1. Certifications for Termination Assemblies

Type	Certification
Type 1	TAs are UL/UL-C listed as suitable for use in Class I; Groups A-D; Division 2 temperature code T4 hazardous locations. They are DEMKO certified EEx nA IIC T4 for use in Zone 2 potentially explosive atmospheres.
Type 2	TAs are UL/UL-C listed as associated apparatus for supplying non-incendive field circuits Class I; Groups A-D; Division 2 hazardous locations when connected to specified 200 Series FBMs and field circuits meeting entity parameter constraints specified in <i>Standard and Compact 200 Series Subsystem User's Guide</i> (B0400FA). They are also DEMKO certified as associated apparatus for supplying field circuits for Group IIC, Zone 2 potentially explosive atmospheres. Field circuits are also Class 2 limited energy (60 V DC, 30 V AC, 100 VA or less) if customer-supplied equipment meets Class 2.

Table 2. Termination Cable Types and Part Numbers

Length m (ft)	Type 4 P/PVC Cable, 26 AWG(a)	Type 4 LSZH(b)
0.5 (1.6)	RH916FG (supersedes P0916FG)	RH928BA (supersedes P0928BA)
1.0 (3.2)	RH916FH (supersedes P0916FH)	RH928BB (supersedes P0928BB)
2.0 (6.6)	RH931RQ (supersedes P0931RQ)	RH928BC (supersedes P0928BC)
3.0 (9.8)	RH916FJ (supersedes P0916FJ)	RH928BD (supersedes P0928BD)
5.0 (16.4)	RH916FK (supersedes P0916FK)	RH928BE (supersedes P0928BE)
10.0 (32.8)	RH916FL (supersedes P0916FL)	RH928BF (supersedes P0928BF)
15.0 (49.2)	RH916FM (supersedes P0916FM)	RH928BG (supersedes P0928BG)
20.0 (65.6)	RH916FN (supersedes P0916FN)	RH928BH (supersedes P0928BH)

Table 2. Termination Cable Types and Part Numbers (Continued)

Length m (ft)	Type 4 P/PVC Cable, 26 AWG^(a)	Type 4 LSZH^(b)
25.0 (82.0)	RH916FP (supersedes P0916FP)	RH928BJ (supersedes P0928BJ)
30.0 (98.4)	RH916FQ (supersedes P0916FQ)	RH928BK (supersedes P0928BK)

(a) P/PVC cable assemblies polyurethane outer jacket and semi-rigid PVC primary conductor insulation temperature range: -20 to +70°C (-4 to 158°F)

(b) Low smoke zero halogen or low smoke free of halogen (LSZH) is a material classification used for cable jacketing. LSZH is composed of thermoplastic or thermoset compounds that emit limited smoke and no halogen when exposed to high sources of heat. Temperature range: -40 to +105°C (-40 to +221°F)