



Honeywell MC-TAOX12 51304335-175

Eight-Point Analog Output Field Termination Assembly

Product scope

- Terminates eight analog output loops on compression terminals.
- Uses the documented Size B coated CE construction.
- Interfaces the HPM analog output processor with field wiring.
- Requires cable, polarity and cabinet-footprint confirmation.

Manufacturer source

Honeywell Experion PKS Control Hardware Planning Guide, official model tables.

This English product record summarizes manufacturer-verified function, operating principle, application and exact-model matching requirements.

Request a fast quote	Product reference	
Email: info@apterpower.com Phone: +86 18106909650 apter.com/inquiry.php	Honeywell MC-TAOX12 51304335-175	

The enclosed manufacturer pages are reproduced without alteration to technical content. External interactive links and unrelated pages are excluded from this web-optimized copy.

Honeywell MC-TAOX12 51304335-175

Eight-Point Analog Output Field Termination Assembly

Manufacturer-source product record

This record consolidates exact-model facts from the manufacturer references listed below. It is included to identify the ordering configuration before the retained source pages.

Analog output points	8 points
24 V DC power draw	171 mA
Output signal class	4 to 20 mA
Terminal type code	C - compression terminals
Mounting size	Size B
FTA function	Analog Output field termination assembly
Conformal coating	Included on MC execution
Compliance execution	CE-compliant part number
Redundant IOP interface	Two IOP cables may terminate at one output FTA
Active-output selection	Automatic selector switch on the FTA
Cabinet role	Field-loop termination for the analog output IOP

Official references

- Honeywell Experion PKS Control Hardware Planning Guide, official model tables.

Only the exact configuration shown above is represented. Adjacent model variants, optional assemblies and system accessories are not treated as part of this ordering identity.

Function, operating principle and application

The notes below explain how this product is used and how its documented signal, power or control path operates. They remain limited to the manufacturer evidence for this model.

Function

The FTA provides the compression-terminal interface between an HPM analog output IOP and eight field output loops.

Operating principle

A dedicated I/O cable carries the channel signals from the processor to the assembly, where each loop is landed and distributed through its assigned terminal path.

Application

It supports orderly cabinet termination for analog actuators and other final-control elements in Honeywell HPM installations.

Replacement boundary

Confirm the coated CE version, Size B footprint, cable assembly and existing loop polarity before moving field conductors.



GLOBAL INDUSTRIAL AUTOMATION SOURCING

Ready to source this part?

Ask for availability, pricing and delivery options.

Request a fast quote

Include the product title and any required part number or quantity.

EMAIL

info@apterpower.com

PHONE

+86 18106909650



SCAN TO CHAT ON WHATSAPP

REQUEST A QUOTE

PRODUCT: Honeywell MC-TAOX12 51304335-175

Manufacturer pages are reproduced without alteration to technical content.

Apter Power is not an authorized distributor, reseller or representative of the products featured.