

Honeywell MC-PAOX03 51304672-150

High-Performance Process Manager Analog Output IOP

Product scope

- Processes eight analog output channels in an HPM control cabinet.
- Includes conformal coating for the documented non-CE execution.
- Works through the matched analog-output field termination assembly.
- Requires channel and cabinet-revision verification before exchange.

Manufacturer source

Honeywell Experion PKS Control Hardware Planning Guide, official model tables.

This English product record summarizes manufacturer-verified function, operating principle, application and exact-model matching requirements.

Request a fast quote	Product reference	
Email: info@apterpower.com Phone: +86 18106909650 apter.com/inquiry.php	Honeywell MC-PAOX03 51304672-150	

The enclosed manufacturer pages are reproduced without alteration to technical content. External interactive links and unrelated pages are excluded from this web-optimized copy.

Honeywell MC-PAOX03 51304672-150

High-Performance Process Manager Analog Output IOP

Manufacturer-source product record

This record consolidates exact-model facts from the manufacturer references listed below. It is included to identify the ordering configuration before the retained source pages.

Analog output channels	8 channels
24 V DC power draw	100 mA
I/O processor type	Analog Output IOP
Conformal coating	Included on MC execution
Compliance execution	Non-CE part number
Redundant operation	Supported by the I/O Link Interface Module
Redundant FTA connection	Separate cable from each IOP to one FTA
Output selection	Automatic selector on the output FTA
Card-file installation	IOP card-file slot
System association	C200 / Process Manager I/O hardware

Official references

- Honeywell Experion PKS Control Hardware Planning Guide, official model tables.

Only the exact configuration shown above is represented. Adjacent model variants, optional assemblies and system accessories are not treated as part of this ordering identity.

Function, operating principle and application

The notes below explain how this product is used and how its documented signal, power or control path operates. They remain limited to the manufacturer evidence for this model.

Function

The IOP receives calculated output values from the controller and manages eight analog output channels for field devices.

Operating principle

Digital output commands are converted and supervised by the IOP before the associated field termination assembly presents the analog signals to the process wiring.

Application

It is used for modulating valves, positioners and other analog final elements in HPM-based control cabinets.

Replacement boundary

The coated non-CE execution must be matched with the installed FTA, cabinet type, channel wiring and HPM revision.



GLOBAL INDUSTRIAL AUTOMATION SOURCING

Ready to source this part?

Ask for availability, pricing and delivery options.

Request a fast quote

Include the product title and any required part number or quantity.

EMAIL

info@apterpower.com

PHONE

+86 18106909650



SCAN TO CHAT ON WHATSAPP

REQUEST A QUOTE

PRODUCT: Honeywell MC-PAOX03 51304672-150

Manufacturer pages are reproduced without alteration to technical content.

Apter Power is not an authorized distributor, reseller or representative of the products featured.