SIEMENS

Data sheet 6ES7134-4NB51-0AB0



*** Spare part *** SIMATIC DP, Electronics module ET 200S: 2AI RTD High Feature, 15 mm width, 15 bit+sign accuracy +/-0.1%, for 2-/3-/4-wire sensors, with internal compensation of the line resistance, with SF LED (group fault)

General information	
Product function	
• Isochronous mode	No
Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V; From power module
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	30 mA
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
• Address space per module, max.	4 byte
Analog inputs	
Number of analog inputs	2
permissible input voltage for voltage input (destruction limit), max.	9 V
Constant measurement current for resistance-type transmitter, typ.	1.25 mA
Cycle time (all channels) max.	Number of active channels per module x basic conversion time
Technical unit for temperature measurement adjustable	Yes
Input ranges (rated values), resistance thermometer	
• Cu 10	Yes
— Input resistance (Cu 10)	10 MΩ
• Ni 100	Yes
— Input resistance (Ni 100)	10 MΩ
• Ni 1000	Yes
— Input resistance (Ni 1000)	10 MΩ
• Ni 120	Yes
— Input resistance (Ni 120)	10 MΩ
• Ni 200	Yes
— Input resistance (Ni 200)	10 MΩ
• Ni 500	Yes
— Input resistance (Ni 500)	10 MΩ
• Pt 100	Yes
— Input resistance (Pt 100)	10 MΩ
• Pt 1000	Yes

Subject to change without notice
© Copyright Siemens

WHATSAPP QUOTE >

— Input resistance (Pt 1000)	10 MΩ
• Pt 200	Yes
— Input resistance (Pt 200)	10 MΩ
• Pt 500	Yes
— Input resistance (Pt 500)	10 MΩ
Input ranges (rated values), resistors	
• 0 to 150 ohms	Yes
— Input resistance (0 to 150 ohms)	10 MΩ
• 0 to 300 ohms	Yes
— Input resistance (0 to 300 ohms)	10 MΩ
• 0 to 600 ohms	Yes
— Input resistance (0 to 600 ohms)	10 MΩ
• 0 to 3000 ohms	Yes
— Input resistance (0 to 3000 ohms)	10 MΩ
Thermocouple (TC)	
Temperature compensation	
— internal temperature compensation	Yes
Characteristic linearization	
• Parameterizable	Yes; for Ptxxx, Nixxx
— for resistance thermometer	Ptxxx, Nixxx
Cable length	
• shielded, max.	200 m
Analog value generation for the inputs	
Measurement principle	integrating (Sigma-Delta)
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit; for Pt100, Ni100, Ni120, Pt200, Ni200, Pt500, Ni500, Pt1000, Ni1000, Cu10: 15 bit + sign; for 150, 300, 600, 3 000 ohms: 15 bit; for PTC: 1 bit
• Integration time (ms)	16,7 / 20 ms
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz
• Conversion time (per channel)	Basic conversion time incl. integration time: 50 / 60 ms; additional conversion time for diagnostics of wire break test: 5 / 5 ms; additional conversion time for line compensation with 3-wire connection: 50 / 60 ms
Smoothing of measured values	
• parameterizable	Yes; In four stages by means of digital filtering
• Step: None	Yes; 1x cycle time
• Step: low	Yes; 4x cycle time
• Step: Medium	Yes; 32x cycle time
• Step: High	Yes; 64x cycle time
Encoder	
Connection of signal encoders	
• for resistance measurement with two-wire connection	Yes
• for resistance measurement with three-wire connection	Yes; internal compensation of the line resistances
• for resistance measurement with four-wire connection	Yes
Errors/accuracies	
Operational error limit in overall temperature range	
• Resistance thermometer, relative to input range, (+/-)	Resistance-type transmitter: ±0.1 %; Pt100, Pt200, Pt500, Pt1000 standard: ±1.0 K; Pt100, Pt200, Pt500, Pt1000 climate: ±0.25 K; Ni100, Ni120, Ni200, Ni500, Ni1000 standard and climate: ±0.4 K; Cu10 ±1.5 K
Basic error limit (operational limit at 25 °C)	
• Resistance thermometer, relative to input range, (+/-)	Resistance-type transmitter: ±0.05 %; Pt100, Pt200, Pt500, Pt1000 standard: ±0.6 K; Pt100, Pt200, Pt500, Pt1000 climate: ±0.13 K; Ni100, Ni120, Ni200, Ni500, Ni1000 standard and climate: ±0.2 K; Cu10 ±1 K
Interrupts/diagnostics/status information	
Diagnoses	
• Wire break	Yes
• Group error	Yes
• Overflow/Underflow	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
Potential separation	

Subject to change without notice
© Copyright Siemens

WHATSAPP QUOTE >

Potential separation analog inputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	40 g

Classifications

	Version	Classification
eClass	16	27-24-26-01
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval





Miscellaneous

Manufacturer Declaration



Metrological Approval

General Product Approval





China RoHS





Manufacturer Declaration

EMV | **For use in hazardous locations**





FM







For use in hazardous locations | **Maritime application**



Miscellaneous

CCC-Ex







Subject to change without notice
© Copyright Siemens

WHATSAPP QUOTE >

Maritime application					
LRS	NK / Nippon Kaiji Kyokai	PRS	RINA	CCS (China Classification Society)	KR (Korean Register of Shipping)

last modified: 8/22/2025

Subject to change without notice
© Copyright Siemens

WHATSAPP QUOTE >

Apter Power

GLOBAL INDUSTRIAL AUTOMATION SOURCING

Ready to source this part?

Ask for availability, pricing and delivery options.

Request a fast quote

Include the product title and any required part number or quantity.

EMAIL

info@apterpower.com

PHONE

+86 18106909650

CHAT ON WHATSAPP >

SCAN TO CHAT ON WHATSAPP

PRODUCT: 6ES7134-4NB51-0AB0 / SIMATIC ET 200S 2AI RTD HF Module

The enclosed manufacturer pages are reproduced without alteration to technical content.

Apter Power is not an authorized distributor, reseller or representative of the products featured.

Product names, trademarks, brands and logos remain the property of their respective owners.